LX3 Expansion Modules

LX3V Module		Specification
I/O	LX3V-8EX/16EX	8 / 16 * Input
	LX3V-8EYR/16EYR	8 / 16 * Relay Output
	LX3V-8EYT/16EYT	8 / 16 * Transistor Output
Analog	LX3V-4AD	4 * Analog Input
	LX3V-4DA	4 * Analog Output
Weighting	LX3V-1WT	1 * Weighing (24-bit)
	LX3V-2WT	2 * Weighing (24-bit)
	LX3V-1WT-L	1 * Weighing (18-bit)
	LX3V-2WT-L	2 * Weighing (18-bit)

LX3V Module		Specification
Temperature	LX3V-4PT	4 * Thermal Resistance Input
	LX3V-4TC	4 * Thermocouple Input
	LX3V-4LTC	4 * TC with Isolation (PID Control)
	LX3V-8iTC	8 thermocouple temperature module
High Speed Pulse Output	LX3V-4PGA	Supports 4*200kHz high-speed pulse output. Supports T, S curve acceleration and deceleration. Supports two-speed positioning and interrupt one-speed positioning. Supports variable speed operation. Supports single-speed positioning.
	LX3V-4PGB	Supports 4*200kHz high-speed pulse output. Supports T curve acceleration and deceleration. Supports single-speed positioning.